

**Code No: 56044**

**Set No. 1**

**JAWAHARLAL NEHRU TECHNOLOGICAL UNIVERSITY HYDERABAD**

**III B.Tech. II Sem., II Mid-Term Examinations, April – 2014**

**INSTRUMENTATION PRACTICES IN INDUSTRIES**

**Objective Exam**

**Name:** \_\_\_\_\_ **Hall Ticket No.**

						A				
--	--	--	--	--	--	---	--	--	--	--

**Answer All Questions. All Questions Carry Equal Marks. Time: 20 Min. Marks: 10.**

**I Choose the correct alternative:**

1. The most frequently used measured variable in power plants are ----- [     ]  
a) Pressure                      b) Temperature                      c) Flow                      d) All of the above
2. Vibration measurement is measured by using ----- [     ]  
a) RTD                      b) Accelerometer                      c) Thermostat                      d) None of the above
3. Coal produces steam in boiler and this steam at ----- temperature and pressure is used to run a turbine generator [     ]  
a) Constant                      b) Low                      c) High                      d) None of the above
4. Aneroid barometer basically consists of ----- [     ]  
a) Pressure sensing elements                      b) A system of gears  
c) A system of levers                      d) All the above
5. A pitot static system is used for the measurement of aircraft ----- [     ]  
a) Speed                      b) Vibration                      c) Temperature                      d) All the above
6. Selective radiation pyrometers are used to measure either ----- range [     ]  
a) Optical                      b) Infrared                      c) Both a& b                      d) None of the above
7. Engine speed cannot be measured by ----- [     ]  
a) AC tachometer                      b) DC tachometer                      c) Both a& b                      d) None of the above
8. Whenever a potential difference is applied across two conducting surfaces separated by a non conducting medium called a dielectric and having the property of storing an electric charge is known as ----- [     ]  
a) Capacitance                      b) Resistance                      c) Inductance                      d) None of the above
9. Interlocking is one which prevents a machine from ----- [     ]  
a) RAT                      b) SAT                      c) Harming                      d) None of the above
10. Boilers should always be brought on line slowly and ----- water should never be added into hot system [     ]  
a) Cold                      b) Hot                      c) Both a& b                      d) None of the above

**Cont....2**

**II Fill in the blanks**

11. Cooling towers are classified as ----- draft and ----- draft.
12. The primary task of cooling towers is to reject ----- into the atmosphere.
13. The variables that are to be measured and monitored continuously in a plant safety are -----
14. A ----- is an instrument, which has a magnet sensing element and heating indicator all in the instrument.
15. A gyroscope has three degrees of freedom and they are -----,----- and -----.
16. Tachometer is used for ----- speed measurement.
17. In Flight Instrumentation, SAT stands for -----
18. A ----- manometer indicates the pressure relative to the atmosphere.
19. An ----- can be defined as a device that prevents you from making inappropriate adjustments.
20. Safety interlock is a method of preventing includes ----- machines.

Name: \_\_\_\_\_ Hall Ticket No. 

						A			
--	--	--	--	--	--	---	--	--	--

**Answer All Questions. All Questions Carry Equal Marks. Time: 20 Min. Marks: 10.****I Choose the correct alternative:**

1. Aneroid barometer basically consists of ----- [      ]  
 a) Pressure sensing elements      b) A system of gears  
 c) A system of levers      d) All the above
2. A pitot static system is used for the measurement of aircraft ----- [      ]  
 a) Speed      b) Vibration      c) Temperature      d) All the above
3. Selective radiation pyrometers are used to measure either ----- range [      ]  
 a) Optical      b) Infrared      c) Both a& b      d) None of the above
4. Engine speed cannot be measured by ----- [      ]  
 a) AC tachometer      b) DC tachometer      c) Both a& b      d) None of the above
5. Whenever a potential difference is applied across two conducting surfaces separated by a non conducting medium called a dielectric and having the property of storing an electric charge is known as ----- [      ]  
 a) Capacitance      b) Resistance      c) Inductance      d) None of the above
6. Interlocking is one which prevents a machine from ----- [      ]  
 a) RAT      b) SAT      c) Harming      d) None of the above
7. Boilers should always be brought on line slowly and ----- water should never be added into hot system [      ]  
 a) Cold      b) Hot      c) Both a& b      d) None of the above
8. The most frequently used measured variable in power plants are ----- [      ]  
 a) Pressure      b) Temperature      c) Flow      d) All of the above
9. Vibration measurement is measured by using ----- [      ]  
 a) RTD      b) Accelerometer      c) Thermostat      d) None of the above
10. Coal produces steam in boiler and this steam at ----- temperature and pressure is used to run a turbine generator [      ]  
 a) Constant      b) Low      c) High      d) None of the above

**II Fill in the blanks**

11. A ----- is an instrument, which has a magnet sensing element and heating indicator all in the instrument.
12. A gyroscope has three degrees of freedom and they are -----,----- and -----.
13. Tachometer is used for ----- speed measurement.
14. In Flight Instrumentation, SAT stands for -----
15. A ----- manometer indicates the pressure relative to the atmosphere.
16. An ----- can be defined as a device that prevents you from making inappropriate adjustments.
17. Safety interlock is a method of preventing includes ----- machines.
18. Cooling towers are classified as ----- draft and ----- draft.
19. The primary task of cooling towers is to reject ----- into the atmosphere.
20. The variables that are to be measured and monitored continuously in a plant safety are -----

Name: \_\_\_\_\_ Hall Ticket No. 

						A			
--	--	--	--	--	--	---	--	--	--

**Answer All Questions. All Questions Carry Equal Marks. Time: 20 Min. Marks: 10.****I Choose the correct alternative:**

1. Selective radiation pyrometers are used to measure either ----- range [      ]  
a) Optical                      b) Infrared                      c) Both a& b                      d) None of the above
2. Engine speed cannot be measured by ----- [      ]  
a) AC tachometer              b) DC tachometer              c) Both a& b                      d) None of the above
3. Whenever a potential difference is applied across two conducting surfaces separated by a non conducting medium called a dielectric and having the property of storing an electric charge is known as ----- [      ]  
a) Capacitance                      b) Resistance                      c) Inductance                      d) None of the above
4. Interlocking is one which prevents a machine from ----- [      ]  
a) RAT                              b) SAT                              c) Harming                      d) None of the above
5. Boilers should always be brought on line slowly and ----- water should never be added into hot system [      ]  
a) Cold                              b) Hot                              c) Both a& b                      d) None of the above
6. The most frequently used measured variable in power plants are ----- [      ]  
a) Pressure                      b) Temperature                      c) Flow                              d) All of the above
7. Vibration measurement is measured by using ----- [      ]  
a) RTD                              b) Accelerometer                      c) Thermostat                      d) None of the above
8. Coal produces steam in boiler and this steam at ----- temperature and pressure is used to run a turbine generator [      ]  
a) Constant                      b) Low                              c) High                              d) None of the above
9. Aneroid barometer basically consists of ----- [      ]  
a) Pressure sensing elements                      b) A system of gears  
c) A system of levers                      d) All the above
10. A pitot static system is used for the measurement of aircraft ----- [      ]  
a) Speed                              b) Vibration                              c) Temperature                      d) All the above

**II Fill in the blanks**

11. Tachometer is used for ----- speed measurement.
12. In Flight Instrumentation, SAT stands for -----
13. A ----- manometer indicates the pressure relative to the atmosphere.
14. An ----- can be defined as a device that prevents you from making inappropriate adjustments.
15. Safety interlock is a method of preventing includes ----- machines.
16. Cooling towers are classified as ----- draft and ----- draft.
17. The primary task of cooling towers is to reject ----- into the atmosphere.
18. The variables that are to be measured and monitored continuously in a plant safety are -----
19. A ----- is an instrument, which has a magnet sensing element and heating indicator all in the instrument.
20. A gyroscope has three degrees of freedom and they are -----,----- and -  
-----.

Name: \_\_\_\_\_ Hall Ticket No. 

						A			
--	--	--	--	--	--	---	--	--	--

**Answer All Questions. All Questions Carry Equal Marks. Time: 20 Min. Marks: 10.****I Choose the correct alternative:**

1. Whenever a potential difference is applied across two conducting surfaces separated by a non conducting medium called a dielectric and having the property of storing an electric charge is known as ----- [     ]  
a) Capacitance                      b) Resistance                      c) Inductance                      d) None of the above
2. Interlocking is one which prevents a machine from ----- [     ]  
a) RAT                                  b) SAT                                  c) Harming                      d) None of the above
3. Boilers should always be brought on line slowly and ----- water should never be added into hot system [     ]  
a) Cold                                  b) Hot                                  c) Both a& b                      d) None of the above
4. The most frequently used measured variable in power plants are ----- [     ]  
a) Pressure                              b) Temperature                      c) Flow                              d) All of the above
5. Vibration measurement is measured by using ----- [     ]  
a) RTD                                  b) Accelerometer                      c) Thermostat                      d) None of the above
6. Coal produces steam in boiler and this steam at ----- temperature and pressure is used to run a turbine generator [     ]  
a) Constant                              b) Low                                  c) High                                  d) None of the above
7. Aneroid barometer basically consists of ----- [     ]  
a) Pressure sensing elements                      b) A system of gears  
c) A system of levers                      d) All the above
8. A pitot static system is used for the measurement of aircraft ----- [     ]  
a) Speed                                  b) Vibration                              c) Temperature                      d) All the above
9. Selective radiation pyrometers are used to measure either ----- range [     ]  
a) Optical                                  b) Infrared                              c) Both a& b                      d) None of the above
10. Engine speed cannot be measured by ----- [     ]  
a) AC tachometer                      b) DC tachometer                      c) Both a& b                      d) None of the above

**II Fill in the blanks**

11. A ----- manometer indicates the pressure relative to the atmosphere.
12. An ----- can be defined as a device that prevents you from making inappropriate adjustments.
13. Safety interlock is a method of preventing includes ----- machines.
14. Cooling towers are classified as ----- draft and ----- draft.
15. The primary task of cooling towers is to reject ----- into the atmosphere.
16. The variables that are to be measured and monitored continuously in a plant safety are -----
17. A ----- is an instrument, which has a magnet sensing element and heating indicator all in the instrument.
18. A gyroscope has three degrees of freedom and they are -----,----- and -----.
19. Tachometer is used for ----- speed measurement.
20. In Flight Instrumentation, SAT stands for -----